




















TECHNICAL DATA - RECESSED 12900




**A UNIQUE LENS**  
The innovative lens offers a uniform light beam with great glare control and optical efficiency.




**AN EFFICIENT AND MINIMALIST DESIGN**  
Without any visible hardware, this simple enclosure puts the focus on the projectors.




**EASY INSTALLATION**  
Outline is quickly and securely installed within the ceiling with the help of spring arms.



**BROAD RANGE OF MOTION**  
Each projector pivots on a magnetic ball joint that keeps all heads centered in the housing, preserving symmetry within the fixture.



**MOUNTING PLATE**  
An optional plate allows for installations on suspended ceiling systems or new constructions.




**ADAPT TO YOUR SPACE**  
Outline's recessed version is offered with 1, 2 or 3 projectors, with or without a trim, to suit your needs.

PRODUCT SPECIFICATION	12900-1X1 REG — HO	12900-2X1 REG — HO	12900-3X1 REG — HO
PERFORMANCE			
SYSTEM WATTAGE	10.1 W — 15.2 W	18.6 W — 29.6 W	27.5 W — 44.6 W
DELIVERED LUMENS (4000K - WHE)	764 LM — 1245 LM	1528 LM — 2486 LM	2292 LM — 3729 LM
EFFICACY	75 LM/W — 82 LM/W	82 LM/W — 84 LM/W	83 LM/W — 84 LM/W
OTHER INFORMATION			
LUMINAIRE'S WEIGHT (UP TO)	3.9 LBS / 1.8 KG	5.5 LBS / 2.5 KG	8.3 LBS / 3.8 KG

**EFFICACY MULTIPLIERS**

CRI	CCT	FACTOR
80+	4000K	1.00
80+	3500K	0.94
80+	3000K	0.94
80+	2700K	0.94
90+	4000K	0.87
90+	3500K	0.81
90+	3000K	0.81
90+	2700K	0.74

**LIGHT DISTRIBUTION**



PROJECTOR



Visit our website for warranty terms and conditions.












# TECHNICAL DATA - SURFACE 46900



**A UNIQUE LENS**  
The innovative lens offers a uniform light beam with great glare control and optical efficiency.




**ADAPT TO YOUR SPACE**  
Outline's surface version is available with 1, 2 or 3 projectors to suit your needs.



**BROAD RANGE OF MOTION**  
Each projector is equipped with a clever pivot that gives it a broad range of rotation and tilt.

**EASY INSTALLATION**  
Outline is quickly and securely installed on the ceiling with the help of spring arms.




PRODUCT SPECIFICATION	46900-1X1 REG — HO	46900-2X1 REG — HO	46900-3X1 REG — HO
PERFORMANCE			
SYSTEM WATTAGE	10.1 W — 15.2 W	18.6 W — 29.6 W	27.5 W — 44.6 W
DELIVERED LUMENS (4000K - WHE)	764 LM — 1245 LM	1528 LM — 2486 LM	2292 LM — 3729 LM
EFFICACY	75 LM/W — 82 LM/W	82 LM/W — 84 LM/W	83 LM/W — 84 LM/W
OTHER INFORMATION			
LUMINAIRE'S WEIGHT (UP TO)	1.1 LBS / 0.5 KG	2.9 LBS / 1.3 KG	4.4 LBS / 2.0 KG

EFFICACY MULTIPLIERS

CRI	CCT	FACTOR
80+	4000K	1.00
80+	3500K	0.94
80+	3000K	0.94
80+	2700K	0.94
90+	4000K	0.87
90+	3500K	0.81
90+	3000K	0.81
90+	2700K	0.74

LIGHT DISTRIBUTION



Visit our website for warranty terms and conditions.





# TECHNICAL DATA - SUSPENDED AIMABLE 74900


**A WELL-BALANCED SUSPENSION**  
Twin suspension cables keep the luminaire leveled and prevent it from tilting when the projectors are oriented.

**A UNIQUE LENS**  
The innovative lens offers a uniform light beam with great glare control and optical efficiency.

**COUNTLESS POSSIBILITIES**  
Outline's suspended version is offered in two lengths, with a variety of projectors configurations to adapt to any space and its needs.

**BROAD RANGE OF MOTION**  
Each projector is equipped with a clever pivot that gives it a broad range of rotation and tilt.

**UPLIGHT**  
Outline is offered with an optional upright source to brighten any space.




PRODUCT SPECIFICATION	PROJECTOR (EACH) LOW — REG	UPLIGHT 54" LOW — REG — HO	UPLIGHT 78" LOW — REG — HO
PERFORMANCE			
SYSTEM WATTAGE	5 W — 8.7 W	15.7 W — 32.3 W — 50.1 W	22.9 W — 47.5 W — 74.5 W
DELIVERED LUMENS (4000K - WHE)	405 LM — 733 LM	1960 LM — 2824 LM — 5580 LM	3005 LM — 5862 LM — 8552 LM
EFFICACY	81 LM/W — 84 LM/W	125 LM/W — 118 LM/W — 111 LM/W	131 LM/W — 123 LM/W — 115 LM/W
OTHER INFORMATION			
LUMINAIRE'S WEIGHT (UP TO)		12.1 LBS / 5.5 KG	15.2 LBS / 6.9 KG

## EFFICACY MULTIPLIERS


CRI	CCT	FACTOR PROJ.	FACTOR UPLIGHT
80+	4000K	1.00	1.00
80+	3500K	0.94	0.98
80+	3000K	0.94	0.94
80+	2700K	0.94	0.91
90+	4000K	0.87	0.88
90+	3500K	0.81	0.85
90+	3000K	0.81	0.81
90+	2700K	0.74	0.77

## LIGHT DISTRIBUTION




Visit our website for warranty terms and conditions.







# TECHNICAL DATA - SUSPENDED FIXED 74901




**A UNIQUE LENS**  
The innovative lens offers a uniform light beam with great glare control and optical efficiency.



**COUNTLESS POSSIBILITIES**  
Outline's suspended version is offered in two lengths, with a variety of projector configurations to adapt to any space and its needs.



**UPLIGHT**  
Outline is offered with an optional uplight source to brighten any space.




**FIXED PROJECTORS**  
Projectors are fixed for downlight applications. Heads are evenly distributed along luminaire or clustered together.

PRODUCT SPECIFICATION	PROJECTOR (EACH) LOW — REG	UPLIGHT 54" LOW — REG — HO	UPLIGHT 78" LOW — REG — HO
PERFORMANCE			
SYSTEM WATTAGE	5 W — 8.7 W	15.7 W — 32.3 W — 50.1 W	22.9 W — 47.5 W — 74.5 W
DELIVERED LUMENS (4000K - WHE)	405 LM — 733 LM	1960 LM — 2824 LM — 5580 LM	3005 LM — 5862 LM — 8552 LM
EFFICACY	81 LM/W — 84 LM/W	125 LM/W — 118 LM/W — 111 LM/W	131 LM/W — 123 LM/W — 115 LM/W
OTHER INFORMATION			
LUMINAIRE'S WEIGHT (UP TO)		12.1 LBS / 5.5 KG	15.2 LBS / 6.9 KG

## EFFICACY MULTIPLIERS

CRI	CCT	FACTOR PROJ.	FACTOR UPLIGHT
80+	4000K	1.00	1.00
80+	3500K	0.94	0.98
80+	3000K	0.94	0.94
80+	2700K	0.94	0.91
90+	4000K	0.87	0.88
90+	3500K	0.81	0.85
90+	3000K	0.81	0.81
90+	2700K	0.74	0.77

## LIGHT DISTRIBUTION



PROJECTOR

UPLIGHT



Visit our website for warranty terms and conditions.









OUTLINE RECESSED 12900

PROJECT PROJECT

SPEC TYPE

NOTES



ORDERING SPECIFICATION    SPÉCIFICATION DE COMMANDE		CODE
MODEL    MODÈLE		
12900-1X1	OUTLINE RECESSED 1X1	
12900-2X1	OUTLINE RECESSED 2X1	
12900-3X1	OUTLINE RECESSED 3X1	
LIGHT SOURCE    SOURCE LUMINEUSE		
LED	REGULAR OUTPUT (IC RATED)	
LED.HO	HIGH OUTPUT (NON-IC RATED)	
COLOR TEMPERATURE    TEMPÉRATURE DE COULEUR		
27*	2700K	
30	3000K	
35	3500K	
40	4000K	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
COLOR RENDERING INDEX (CRI)    INDICE DE RENDU DE COULEUR (IRC)		
80	80+ CRI	
90*	90+ CRI	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
VOLTAGE    VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
DIMMING OPTION    OPTION DE GRADATION		
DV	0-10V DIMMING (120V-277V)	
DP	PHASE DIMMING (120V ONLY)	
LED DIMMING DRIVER IS STANDARD IN THIS PRODUCT, PLEASE SPECIFY YOUR DIMMING TYPE		
EMERGENCY BATTERY    BATTERIE D'URGENCE		
INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.		
EMB*	EMERGENCY BATTERY FOR REMOTE BOX	
* 3981EA ACCESSORY IS REQUIRED		
BEAM ANGLE    ANGLE DE FAISCEAU		ME
ME	MEDIUM (30°)	
MOUNTING    MONTAGE		
WT	WITH TRIM	
NT	TRIMLESS (DRYWALL MUD FLANGE)	
TRIM FINISH    FINI CADRE <sup>(A)</sup>		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
<sup>(A)</sup> AVAILABLE WITH TRIM OPTION ONLY		
PROJECTOR FINISH    FINI PROJECTEURS		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
ENCLOSURE FINISH    FINI BOÎTIER		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
ACCESSORY    ACCESSOIRE		
19900-1X1	NEW CONSTRUCTION MOUNTING PLATE (FOR 12900-1X1)	
19900-2X1	NEW CONSTRUCTION MOUNTING PLATE (FOR 12900-2X1)	
19900-3X1	NEW CONSTRUCTION MOUNTING PLATE (FOR 12900-3X1)	
EMERGENCY BATTERY ACCESSORY    ACCESSOIRE BATTERIE D'URGENCE		
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY	

PRODUCT CHARACTERISTICS    CARACTÉRISTIQUES DU PRODUIT

BIM

DIM

EMB

IES

LED

360° +

40°

1X1 – 6.20" (158mm) X 6.20" (158mm)  
2X1 – 11.35" (288mm) X 6.20" (158mm)  
3X1 – 16.50" (419mm) X 6.20" (158mm)

DESIGN :	Outline is a modern and distinctive luminaire that creates a bold graphic statement. It exhibits a willingness to challenge traditional notions of projector-type lighting design. Without any visible hardware, the simple enclosure of the recessed version puts the focus on the projectors.
INSTALLATION :	With a simple push, Outline easily secures itself within the ceiling hole for a safe and quick installation. The Outline is suitable for new construction, remodeling and grid ceiling installation. For a seamless look, a trimless option is available.
STRUCTURE :	A sturdy steel housing and injected aluminium projector heads coated in a high-quality fine texture finish.
OPTIC :	The patent-pending Halo lens combined with the glare-control ring create a uniform light beam with a smooth cut-off.
CERTIFIED :	c-CSA-us

OUTLINE SURFACE 46900

PROJECT	PROJET
SPEC TYPE	
NOTES	



FINISH FINI




BLKE WHE

FAMILY FAMILLE




RECESSED (12900) SUSPENDED AIMABLE (74900) SUSPENDED FIXED (74901)



ORDERING SPECIFICATION	SPÉCIFICATION DE COMMANDE	CODE
MODEL	MODÈLE	
46900-1X1	OUTLINE SURFACE 1X1	
46900-2X1	OUTLINE SURFACE 2X1	
46900-3X1	OUTLINE SURFACE 3X1	
LIGHT SOURCE	SOURCE LUMINEUSE	
LED	REGULAR OUTPUT (IC RATED)	
LED.HO	HIGH OUTPUT (NON-IC RATED)	
COLOR TEMPERATURE	TEMPÉRATURE DE COULEUR	
27*	2700K	
30	3000K	
35	3500K	
40	4000K	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
COLOR RENDERING INDEX (CRI)	INDICE DE RENDU DE COULEUR (IRC)	
80	80+ CRI	
90*	90+ CRI	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
VOLTAGE	VOLTAGE	
120V	120 VOLT	
277V	277 VOLT	
DIMMING OPTION	OPTION DE GRADATION	
DV	0-10V DIMMING (120V-277V)	
DP	PHASE DIMMING (120V ONLY)	
LED DIMMING DRIVER IS STANDARD IN THIS PRODUCT, PLEASE SPECIFY YOUR DIMMING TYPE		
EMERGENCY BATTERY	BATTERIE D'URGENCE	
INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.		
EMB*	EMERGENCY BATTERY FOR REMOTE BOX	
* 3981EA ACCESSORY IS REQUIRED		
BEAM ANGLE	ANGLE DE FAISCEAU	ME
ME	MEDIUM (30°)	
ENCLOSURE FINISH	FINI BOÎTIER	
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
EMERGENCY BATTERY ACCESSORY	ACCESSOIRE BATTERIE D'URGENCE	
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY	

PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT



DESIGN :	Outline is a modern and distinctive luminaire that creates a bold graphic statement. It exhibits a willingness to challenge traditional notions of projector-type lighting design. Each projector is equipped with a pivot that gives it a broad range of rotation and tilt. With its recessed driver and connection box, the Outline surface version is quickly and securely installed on the ceiling with spring arms.
INSTALLATION :	A machined plate and injected aluminium projectors coated in a high-quality fine texture finish. The patent-pending Halo lens combined with the glare-control ring create a uniform light beam with a smooth cut-off.
STRUCTURE :	c-CSA-us
CERTIFIED :	
CONCEPTION :	Outline est un luminaire au design moderne, distinctif et graphique, qui redéfinit le concept typique de projecteur. Sa grande liberté d'orientation lui permet de mettre en valeur autant un mur qu'un couloir, et tout ce qui se trouve entre les deux.
INSTALLATION :	Grâce à la boîte de connexion encastrée et le système de bras à ressort, la version surface s'installe facilement et rapidement.
STRUCTURE :	Une plaque machinée jumelée à des projecteurs en aluminium revêtus d'une finition à texture fine de haute qualité.
OPTIQUE :	La lentille Halo en attente de brevet et l'anneau anti-éblouissement produisent un faisceau de lumière parfaitement contrôlé avec une coupure en douceur.
CERTIFIÉ :	c-CSA-us



OUTLINE SUSPENDED AIMABLE 74900

PROJECT PROJECT

SPEC TYPE

NOTES



FINISH FINI



BLKE

WHE


FAMILY FAMILLE



RECESSED (12900)

SURFACE (46900)

SUSPENDED FIXED (74901)



PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT

BIM

DIM

EMB

IES

LED

2 CIRCUITS

358°

70°

CERTIFIED: c-CSA-us.



ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE		CODE
MODEL MODÈLE		74900
74900	OUTLINE SUSPENDED AIMABLE	
LIGHT SOURCE DIRECTION DIRECTION DE LA SOURCE LUMINEUSE		
D	DIRECT	
DI *	DIRECT & INDIRECT (DUAL DIMMING)	
* DOWNLIGHT AND UPLIGHT ARE DIMMED INDEPENDENTLY		
LUMINAIRE LENGTH LONGUEUR DU LUMINAIRE		
54	54"	
78	78"	
PROJECTOR CONFIGURATIONS CONFIGURATIONS DE PROJECTEURS		
	54"	
2X2	2 CLUSTERS OF 2 PROJECTORS – TOTAL OF 4	
3X2	3 CLUSTERS OF 2 PROJECTORS – TOTAL OF 6	
2X3	2 CLUSTERS OF 3 PROJECTORS – TOTAL OF 6	
	78"	
3X2	3 CLUSTERS OF 2 PROJECTORS – TOTAL OF 6	
4X2	4 CLUSTERS OF 2 PROJECTORS – TOTAL OF 8	
2X3	2 CLUSTERS OF 3 PROJECTORS – TOTAL OF 6	
3X3 *	3 CLUSTERS OF 3 PROJECTORS – TOTAL OF 9	
PROJECTOR LIGHT SOURCE SOURCE LUMINEUSE PROJECTEURS		
LED.LO	LOW OUTPUT	
LED	REGULAR OUTPUT	
INDIRECT LIGHT SOURCE SOURCE LUMINEUSE INDIRECTE		
LED.LO	LOW OUTPUT	
LED	REGULAR OUTPUT	
LED.HO	HIGH OUTPUT	
COLOR TEMPERATURE TEMPÉRATURE DE COULEUR		
27 *	2700K	
30	3000K	
35	3500K	
40	4000K	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)		
80	80+ CRI	
90 *	90+ CRI	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
VOLTAGE VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
DIMMING OPTION OPTION DE GRADATION		DV
DV	0-10V DIMMING (120V-277V)	
EMERGENCY BATTERY BATTERIE D'URGENCE		
INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.		
EMB *	EMERGENCY BATTERY FOR REMOTE BOX	
* 3981EA ACCESSORY IS REQUIRED		
BEAM ANGLE ANGLE DE FAISCEAU		ME
ME	MEDIUM (30°)	
CABLE CÂBLE		C
C *	BLACK OR WHITE CABLE, FIELD ADJUSTABLE	
* CABLE FINISH IS COLOR MATCHING BODY FINISH		
CABLE LENGTH LONGUEUR DE CÂBLE		
60	60" CABLE (STD LENGTH)	
**	CUSTOM CABLE LENGTH (PLEASE SPECIFY)	
FOR OVERALL LENGTH, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
MOUNTING MONTAGE		
REC	RECTANGULAR CANOPY / PAVILLON RECTANGULAIRE	
CANOPY FINISH FINI PAVILLON <sup>(A)</sup>		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
<sup>(A)</sup> CEILING GRIPPER BLOCS FINISH ARE COLOR MATCHING CANOPY FINISH		
STRUCTURE FINISH FINI STRUCTURE <sup>(B)</sup>		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
<sup>(B)</sup> PROJECTOR FINISH ARE COLOR MATCHING STRUCTURE FINISH		
EMERGENCY BATTERY ACCESSORY ACCESSOIRE BATTERIE D'URGENCE		
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY	

OUTLINE SUSPENDED FIXED 74901

PROJECT PROJECT

SPEC TYPE

NOTES



FINISH FINI



BLKE

WHE


FAMILY FAMILLE



RECESSED (12900)

SURFACE (46900)

SUSPENDED AIMABLE (74900)



PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT

BIM

DIM

EMB

IES

LED

2

CIRCUITS

CERTIFIED: c-CSA-us

ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE		CODE
MODEL MODÈLE		74901
74901	OUTLINE SUSPENDED FIXED	
LIGHT SOURCE DIRECTION DIRECTION DE LA SOURCE LUMINEUSE		
D	DIRECT	
DI *	DIRECT & INDIRECT (DUAL DIMMING)	
	* DOWNLIGHT AND UPLIGHT ARE DIMMED INDEPENDENTLY	
LUMINAIRE LENGTH LONGUEUR DU LUMINAIRE		
54	54"	
78	78"	
PROJECTOR CONFIGURATIONS CONFIGURATIONS DE PROJECTEURS		
	54"	
4X1	4 INDIVIDUAL PROJECTORS	
6X1	6 INDIVIDUAL PROJECTORS	
2X2	2 CLUSTERS OF 2 PROJECTORS – TOTAL OF 4	
3X2	3 CLUSTERS OF 2 PROJECTORS – TOTAL OF 6	
2X3	2 CLUSTERS OF 3 PROJECTORS – TOTAL OF 6	
	78"	
6X1	6 INDIVIDUAL PROJECTORS	
9X1	9 INDIVIDUAL PROJECTORS	
3X2	3 CLUSTERS OF 2 PROJECTORS – TOTAL OF 6	
4X2	4 CLUSTERS OF 2 PROJECTORS – TOTAL OF 8	
2X3	2 CLUSTERS OF 3 PROJECTORS – TOTAL OF 6	
3X3	3 CLUSTERS OF 3 PROJECTORS – TOTAL OF 9	
PROJECTOR LIGHT SOURCE SOURCE LUMINEUSE PROJECTEURS		
LED.LO	LOW OUTPUT	
LED	REGULAR OUTPUT	
INDIRECT LIGHT SOURCE SOURCE LUMINEUSE INDIRECTE		
LED.LO	LOW OUTPUT	
LED	REGULAR OUTPUT	
LED.HO	HIGH OUTPUT	
COLOR TEMPERATURE TEMPÉRATURE DE COULEUR		
27 *	2700K	
30	3000K	
35	3500K	
40	4000K	
	* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)		
80	80+ CRI	
90 *	90+ CRI	
	* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
VOLTAGE VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
DIMMING OPTION OPTION DE GRADATION		DV
DV	0-10V DIMMING (120V-277V)	
EMERGENCY BATTERY BATTERIE D'URGENCE		
INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.		
EMB *	EMERGENCY BATTERY FOR REMOTE BOX	
	* 3981EA ACCESSORY IS REQUIRED	
BEAM ANGLE ANGLE DE FAISCEAU		ME
ME	MEDIUM (30°)	
CABLE CÂBLE		C
C *	BLACK OR WHITE CABLE, FIELD ADJUSTABLE	
	* CABLE FINISH IS COLOR MATCHING BODY FINISH	
CABLE LENGTH LONGUEUR DE CÂBLE		
60	60" CABLE (STD LENGTH)	
**	CUSTOM CABLE LENGTH (PLEASE SPECIFY)	
	FOR OVERALL LENGTH, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
MOUNTING MONTAGE		
REC	RECTANGULAR CANOPY / PAVILLON RECTANGULAIRE – 18.75" X 4.5" X 1.5"	
CANOPY FINISH FINI PAVILLON <sup>(A)</sup>		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
	<sup>(A)</sup> CEILING GRIPPER BLOCS FINISH ARE COLOR MATCHING CANOPY FINISH	
STRUCTURE FINISH FINI STRUCTURE <sup>(B)</sup>		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
	<sup>(B)</sup> PROJECTOR FINISH ARE COLOR MATCHING STRUCTURE FINISH	
EMERGENCY BATTERY ACCESSORY ACCESSOIRE BATTERIE D'URGENCE		
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY	

# PHOTOMETRIC REPORT

## SINGLE PROJECTOR LOW

CCT (K): 4000  
Delivered Lumens (lm): 405  
System wattage (W)\*: 5.0  
Distribution: Direct  
Delivered Efficacy (lm/W): 81  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.5 (88)  
90-270 Axis: 3.5 (88)  
Height: 0.0 (0)

Luminaire spacing criteria  
2 luminaires, plane 0: 0.54  
2 luminaires, plane 90: 0.54  
4 luminaires: 0.58

## SINGLE PROJECTOR REG

CCT (K): 4000  
Delivered Lumens (lm): 733  
System wattage (W)\*: 8.7  
Distribution: Direct  
Delivered Efficacy (lm/W): 84  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.5 (88)  
90-270 Axis: 3.5 (88)  
Height: 0.0 (0)

Luminaire spacing criteria  
2 luminaires, plane 0: 0.54  
2 luminaires, plane 90: 0.54  
4 luminaires: 0.58




## SINGLE PROJECTOR HO

CCT (K): 4000  
Delivered Lumens (lm): 1245  
System wattage (W)\*: 14.8  
Distribution: Direct  
Delivered Efficacy (lm/W): 84  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.5 (88)  
90-270 Axis: 3.5 (88)  
Height: 0.0 (0)

Luminaire spacing criteria  
2 luminaires, plane 0: 0.54  
2 luminaires, plane 90: 0.54  
4 luminaires: 0.58

\*System wattage include driver and LED module consumption



This photometric report has been generated using methods recommended by the IESNA. Calculations are based on simulated photometric data and can change without notice. End-user environment and application (including, but not limited to, voltage variation and dirt accumulation) can cause actual photometric performance to differ from the performance calculated using the data provided by the manufacturer. In no event will Eureka Lighting be responsible for any loss resulting from any use of this report.





# PHOTOMETRIC REPORT

## 7490XDI-78 UPLIGHT LOW

CCT (K): 4000  
Delivered Lumens (lm): 3005  
System wattage (W)\*: 22.9  
Distribution: Indirect  
Delivered Efficacy (lm/W): 131  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.9 (100)  
90-270 Axis: 78.7 (2000)  
Height: 0.0 (0)

## 7490XDI-78 UPLIGHT REG

CCT (K): 4000  
Delivered Lumens (lm): 5862  
System wattage (W)\*: 47.5  
Distribution: Indirect  
Delivered Efficacy (lm/W): 123  
Photometric type C




Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.9 (100)  
90-270 Axis: 78.7 (2000)  
Height: 0.0 (0)

## 7490XDI-78 UPLIGHT HO

CCT (K): 4000  
Delivered Lumens (lm): 8552  
System wattage (W)\*: 74.5  
Distribution: Indirect  
Delivered Efficacy (lm/W): 115  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.9 (100)  
90-270 Axis: 78.7 (2000)  
Height: 0.0 (0)

\*System wattage include driver and LED module consumption



This photometric report has been generated using methods recommended by the IESNA. Calculations are based on simulated photometric data and can change without notice. End-user environment and application (including, but not limited to, voltage variation and dirt accumulation) can cause actual photometric performance to differ from the performance calculated using the data provided by the manufacturer. In no event will Eureka Lighting be responsible for any loss resulting from any use of this report.





# PHOTOMETRIC REPORT

## 7490XDI-54 UPLIGHT LOW

CCT (K): 4000  
Delivered Lumens (lm): 1960  
System wattage (W)\*: 15.7  
Distribution: Indirect  
Delivered Efficacy (lm/W): 125  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.9 (100)  
90-270 Axis: 55.1 (1400)  
Height: 0.0 (0)

\*System wattage include driver and LED module consumption

## 7490XDI-54 UPLIGHT REG




CCT (K): 4000  
Delivered Lumens (lm): 2824  
System wattage (W)\*: 32.3  
Distribution: Indirect  
Delivered Efficacy (lm/W): 118  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.9 (100)  
90-270 Axis: 55.1 (1400)  
Height: 0.0 (0)

## 7490XDI-54 UPLIGHT HO

CCT (K): 4000  
Delivered Lumens (lm): 5580  
System wattage (W)\*: 50.1  
Distribution: Indirect  
Delivered Efficacy (lm/W): 111  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 3.9 (100)  
90-270 Axis: 55.1 (1400)  
Height: 0.0 (0)



This photometric report has been generated using methods recommended by the IESNA. Calculations are based on simulated photometric data and can change without notice. End-user environment and application (including, but not limited to, voltage variation and dirt accumulation) can cause actual photometric performance to differ from the performance calculated using the data provided by the manufacturer. In no event will Eureka Lighting be responsible for any loss resulting from any use of this report.



