

OUTLINE SURFACE 46900

PROJECT PROJÉT

SPEC TYPE



NOTES



FINISH FINI



FAMILY FAMILLE



ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE		CODE
MODEL MODÈLE		
46900-1X1	OUTLINE SURFACE 1X1	
46900-2X1	OUTLINE SURFACE 2X1	
46900-3X1	OUTLINE SURFACE 3X1	
LIGHT SOURCE SOURCE LUMINEUSE		
LED	REGULAR OUTPUT (IC RATED)	
LED.HO	HIGH OUTPUT (NON-IC RATED)	
COLOR TEMPERATURE TEMPÉRATURE DE COULEUR		
27*	2700K	
30	3000K	
35	3500K	
40	4000K	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)		
80	80+ CRI	
90*	90+ CRI	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
VOLTAGE VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
DIMMING OPTION OPTION DE GRADATION		
DV	0-10V DIMMING (120V-277V)	
DP	PHASE DIMMING (120V ONLY)	
LED DIMMING DRIVER IS STANDARD IN THIS PRODUCT, PLEASE SPECIFY YOUR DIMMING TYPE		
EMERGENCY BATTERY BATTERIE D'URGENCE		
INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.		
EMB*	EMERGENCY BATTERY FOR REMOTE BOX	
* 3981EA ACCESSORY IS REQUIRED		
BEAM ANGLE ANGLE DE FAISCEAU		ME
ME	MEDIUM (30°)	
ENCLOSURE FINISH FINI BOÎTIER		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
EMERGENCY BATTERY ACCESSORY ACCESSOIRE BATTERIE D'URGENCE		
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY	

PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT

BIM

DIM

EMB

IES

LED

358°

70°


1X1 – 0.3.125" (80mm)

2X1 – 7" (180mm) X 2" (50mm)

3X1 – 12" (305mm) X 2" (50mm)


DESIGN:	Outline is a modern and distinctive luminaire that creates a bold graphic statement. It exhibits a willingness to challenge traditional notions of projector-type lighting design. Each projector is equipped with a pivot that gives it a broad range of rotation and tilt. With its recessed driver and connection box, the Outline surface version is quickly and securely installed on the ceiling with spring arms.
INSTALLATION:	A machined plate and injected aluminium projectors coated in a high-quality fine texture finish. The patent-pending Halo lens combined with the glare-control ring create a uniform light beam with a smooth cut-off.
STRUCTURE:	c-CSA-us
CERTIFIED:	
CONCEPTION:	Outline est un luminaire au design moderne, distinctif et graphique, qui redéfinit le concept typique de projecteur. Sa grande liberté d'orientation lui permet de mettre en valeur autant un mur qu'un couloir, et tout ce qui se trouve entre les deux. Grâce à la boîte de connexion encastrée et le système de bras à ressort, la version surface s'installe facilement et rapidement.
INSTALLATION:	Une plaque machinée jumelée à des projecteurs en aluminium revêtus d'une finition à texture fine de haute qualité. La lentille Halo en attente de brevet et l'anneau anti-éblouissement produisent un faisceau de lumière parfaitement contrôlé avec une coupure en douceur.
STRUCTURE:	c-CSA-us
OPTIQUE:	
CERTIFIÉ:	

OUTLINE SURFACE 46900




A UNIQUE LENS
The innovative lens offers a uniform light beam with great glare control and optical efficiency.

ADAPT TO YOUR SPACE
Outline's surface version is available with 1, 2 or 3 projectors to suit your needs.



BROAD RANGE OF MOTION
Each projector is equipped with a clever pivot that gives it a broad range of rotation and tilt.

EASY INSTALLATION
Outline is quickly and securely installed on the ceiling with the help of spring arms.




PRODUCT SPECIFICATION	46900-1X1 REG — HO	46900-2X1 REG — HO	46900-3X1 REG — HO
PERFORMANCE			
SYSTEM WATTAGE	10.1 W — 15.2 W	18.6 W — 29.6 W	27.5 W — 44.6 W
DELIVERED LUMENS (4000K - WHE)	764 LM — 1245 LM	1528 LM — 2486 LM	2292 LM — 3729 LM
EFFICACY	75 LM/W — 82 LM/W	82 LM/W — 84 LM/W	83 LM/W — 84 LM/W
OTHER INFORMATION			
LUMINAIRE'S WEIGHT (UP TO)	1.1 LBS / 0.5 KG	2.9 LBS / 1.3 KG	4.4 LBS / 2.0 KG

EFFICACY MULTIPLIERS

CRI	CCT	FACTOR
80+	4000K	1.00
80+	3500K	0.94
80+	3000K	0.94
80+	2700K	0.94
90+	4000K	0.87
90+	3500K	0.81
90+	3000K	0.81
90+	2700K	0.74

LIGHT DISTRIBUTION




UL[®] FCC

5 years warranty

Visit our website for warranty terms and conditions.

OUTLINE SURFACE 46900




SPÉCIFICATION PRODUIT	46900-1X1 REG — HO	46900-2X1 REG — HO	46900-3X1 REG — HO
PERFORMANCE			
PUISSANCE TOTALE	10.1 W — 15.2 W	18.6 W — 29.6 W	27.5 W — 44.6 W
LUMENS RÉELS (4000K-WHE)	764 LM — 1245 LM	1528 LM — 2486 LM	2292 LM — 3729 LM
EFFICACITÉ	75 LM/W — 82 LM/W	82 LM/W — 84 LM/W	83 LM/W — 84 LM/W
AUTRE INFORMATION			
POIDS DU LUMINAIRE (JUSQU'À)	1.1 LBS / 0.5 KG	2.9 LBS / 1.3 KG	4.4 LBS / 2.0 KG

FACTEUR D'EFFICACITÉ

IRC	CCT	FACTEUR
80+	4000K	1.00
80+	3500K	0.94
80+	3000K	0.94
80+	2700K	0.94
90+	4000K	0.87
90+	3500K	0.81
90+	3000K	0.81
90+	2700K	0.74

DISTRIBUTION LUMINEUSE





5 ans de garantie

Visitez notre site Web pour les termes et conditions.